

30000BG Hydraulic Oil HLP 46

Document version: Mar 17, 2024

Description

This mineral multi-functional hydraulic oil has a very broad application scope, and is suitable for use in a wide range of hydraulic and industrial equipment. The blend additive package in this MPM hydraulic oil aids in reducing corrosion, foaming and ensures wear is kept to a minimum.

According to the specifications of

DIN 51524 Part 2 HLP

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 30005BG | 5 L | 4 | 112 |
| 30020BG | 20 L | 1 | 30 |
| 30060BG | 60 L | 1 | 6 |
| 30205BG | 205 L | 1 | 2 |
| 30999BG | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|--|-----------------|------------------------|--------|
| Density at 15°C Kinematic Viscosity at 40°C Kinematic Viscosity at 100°C | 0.878 46.6 | kg/l mm2/s mm2/s | |
| Viscosity Index Flashpoint COC | 7 107 220 | °C | |
| Pourpoint Typical FZG A/8.3/90 | -33 12 | °C level | |

These characteristics are typical of current production. Variations in these characteristics may occur.