



Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 5-3-2020 Revision date: 27-8-2020 Supersedes: 5-3-2020 version: 4.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Motor Oil SAE 20W-20 Super Single Grade
Product code : 41000B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Automotive care products
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
Cyclotronweg 1
2629 HN Delft Delft - Nederland
T +31 (0)15 2514030 - F +31 (0)15 2514031
msds@mpmoil.nl - www.mpmoil.nl

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Highly refined mineral oil, contains <3% (w / w) DMSO extract, according to IP346

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-xx	25 – 50	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312

Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6	25 – 50	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Lubricating oils Baseoil - unspecified	(CAS-No.) 74869-22-0 (EC-No.) 278-012-2 (EC Index-No.) 649-484-00-0	1 – 5	Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation	: No special protection required.
After skin contact	: Gently wash with plenty of soap and water.
After eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes.
After ingestion	: Rinse mouth out with water. Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry chemical, CO ₂ , dry sand, or alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Exercise caution when fighting any chemical fire. Do not enter fire area without proper protective equipment, including respiratory protection. Use a water spray to cool exposed surfaces and to protect fire-fighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing and gloves.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
Other information	: If spilled, may cause the floor to be slippery.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required. Prevent the formation of oil mist.
Handling temperature	: < 40 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage temperature	: < 40 °C
Storage area	: Store in a closed container. Keep in a cool, well-ventilated place.

7.3. Specific end use(s)

No additional information available

Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

EU	IOELV TWA (mg/m ³)	5
EU	IOELV STEL (mg/m ³)	10 mg/m ³
Germany	TRGS 910 Acceptable concentration notes	

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m³ oilspray (TWA, 8 hour workday) is recommended.

8.2. Exposure controls

Personal protective equipment:

Gloves. Safety glasses.

Hand protection:

Wear suitable gloves resistant to chemical penetration

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.35		

Eye protection:

Safety goggles

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

Provide local exhaust or general room ventilation

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily.
Colour	: amber.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 210 °C ASTM D 92
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 886 g/l @ 15°C
Solubility	: Slightly soluble, the product remains on the water surface.
Log Pow	: No data available
Viscosity, kinematic	: 59,5 mm ² /s @ 100°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available

Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Oxidising properties : No data available

Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

acids and bases. Oxidizing agent.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

LD50 oral rat	> 5000 mg/kg bodyweight
LD50 oral	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	5,53 mg/l/4h

Lubricating oils Baseoil - unspecified (74869-22-0)

LD50 oral rat	> 5000 mg/kg bw/day
---------------	---------------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

LD50 oral rat	2000 mg/kg
LD50 dermal rat	2000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	5,53 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 980 mg/l/6h/day
NOAEL (subchronic, oral, animal/male, 90 days)	≥ 2000 mg/kg bodyweight
NOAEL (subchronic, oral, animal/female, 90 days)	≥ 2000 mg/kg bodyweight

Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Lubricating oils Baseoil - unspecified (74869-22-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight OECD 410
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 980 mg/l/6h/day
NOAEL (subchronic, oral, animal/male, 90 days)	≥ 2000 mg/kg bodyweight
NOAEL (subchronic, oral, animal/female, 90 days)	≥ 2000 mg/kg bodyweight

Aspiration hazard : Not classified

Motor Oil SAE 20W-20 Super Single Grade

Viscosity, kinematic 59,5 mm²/s @ 100°C

Other information : This product is formulated with highly refined mineral oils which are considered under IARC as not carcinogenic. It was the IP 346 test showed that all oils in this product contains less than 3% extractable substances.

SECTION 12: Ecological information

12.1. Toxicity

General : Danger of drinking-water pollution (ground water). Contain the spilled material by bunding.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

LC50 fish 1	74 mg/l
EC50 72h algae (1)	3 mg/l

12.2. Persistence and degradability

Motor Oil SAE 20W-20 Super Single Grade

Persistence and degradability Not soluble in water, so only minimally biodegradable.

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

Log Pow > 3

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

Bioconcentration factor (BCF REACH)	260
Log Pow	9,2

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste disposal recommendations : Remove to an authorized waste treatment plant.

Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG
14.1. UN number	
Not applicable	Not applicable
14.2. UN proper shipping name	
Not applicable	Not applicable
14.3. Transport hazard class(es)	
Not applicable	Not applicable
14.4. Packing group	
Not applicable	Not applicable
14.5. Environmental hazards	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

Motor Oil SAE 20W-20 Super Single Grade

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.