

05000DX1-FE Motor Oil 5W-20 Premium Synthetic DX1 Fuel Economy

Document version: Mar 16, 2024



Description

According to the specifications of

Packaging units

This premium synthetic motor oil is specially formulated to meet the latest requirements for petrol engines of passenger cars, light commercial vehicles and SUVs. Particularly developed for the American and Asian markets. This fully synthetic engine oil offers total engine protection and keeps the engine clean even under the most severe conditions. Due to the good friction properties, MPG is enhanced. In addition, because of the excellent thin-flowability, this engine oil offers excellent cold start properties.

API SN Plus / SN-RC / SP / SP-RC Chrysler MS-6395 Fiat 9.55535-CR1 Ford WSS-M2C945-A ILSAC GF-6A Opel/GM dexos1 Gen 2

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001DX1-FE	1 L	6	450
05004DX1-FE	4 L	4	112
05005DX1-FE	5 L	4	112
05020DX1-FE	20 L	1	30
05060DX1-FE	60 L	1	6
05205DX1-FE	205 L	1	2
05999DX1-FE	1000 L	1	-
P05000DX1-FE	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.846	kg/l	ASTM D4052
Viscosity	5W-20		
Kinematic Viscosity at 40°C	45.1	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	8.48	mm2/s	ASTM D445
Viscosity Index	168		ASTM
·			D2270
Flashpoint COC	230	°C	ASTM D92
Pourpoint	-39	°C	ASTM D97
Total Base Number	8.5	mgKOH/g	ASTM
			D2896

These characteristics are typical of current production. Variations in these characteristics may occur.