

51000C Fork Oil Medium Heavy 15W Premium Synthetic

Document version: 16 Mar 2024



Description

MPM Motorcycle Fork Oil Medium Heavy 15W Premium Synthetic is specially developed for use in telescopic front forks for mopeds and road/off road motorcycles. The high deaeration properties of this fork oil means that there is minimum reduced foaming in the fork legs bodies. This gives optimal performance and stability so it will maintain optimal performance under extreme road/off-road conditions. MPM 15W Fork Oil provides excellent protection against wear and corrosion of suspension elements and seals, resulting in a higher performance level.

Note: Also suitable for telescopic forks of mountain bikes and bicycles where a SAE 15W oil is required.

According to the specifications of

ecifications of

Packaging units

SAE 15W

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 51001C | 1 L | 6 | 450 |
| 51020C | 20 L | 1 | 30 |
| 51060C | 60 L | 1 | 6 |
| 51205C | 205 L | 1 | 2 |
| 51999C | 1000 I | 1 | <u>-</u> |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|-------------|-------|-----------------|
| Density at 15°C | 0.855 | kg/l | ASTM D4052 |
| Colour Viscosity | Blue 15W | | VISUAL |
| Kinematic Viscosity at 40°C | 43.2 | mm2/s | ASTM D445 |
| Kinematic Viscosity at 100°C | 8.62 | mm2/s | ASTM D445 |
| Viscosity Index | 183 | | ASTM |
| Pourpoint | -48 | °C | D2270 ASTM D |

These characteristics are typical of current production. Variations in these characteristics may occur.