

05000ST Motor Oil 5W-30 Premium Synthetic ST

Document version: Apr 7, 2024



Description

This Premium Synthetic 'Mid SAPS' engine oil is designed for gasoline and diesel engines equipped with an exhaust after-treatment system. This special formulation complies to the Stellantis FWP9.55535/03 specification which is mandatory for DV5R engines until OPR 16885. These D5VR engines are used in Citroën, DS, Peugeot, Fiat, Toyota, Opel and Vauxhall. The optimized cleanliness, reduces wear increases the lifetime of the mechanical components and the engine. This engine oil is also suitable for engines requiring PSA B71 2290 specification with viscosity grade 5W-30.

Application manual

According to the specifications of

ACEA C3 API SN Plus PSA B71 2290 Stellantis FPW9.55535/03

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001ST	1 L	6	450
05005ST	5 L	4	112
05020ST	20 L	1	30
05060ST	60 L	1	6
05205ST	205 L	1	2
P05000ST	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.847	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	66.3	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	11.3	mm2/s	ASTM D445
Viscosity Index	170		ASTM 2270
Flashpoint COC	254	°C	ASTM D92
Pourpoint	-42	°C	ASTM D97

These characteristics are typical of current production. Variations in these characteristics may occur.