



## 20000LV Brake Fluid Low Viscosity DOT 4+ LV

Document version: Sep 16, 2019



### Description

This synthetic DOT 4+ Low Viscosity brake fluid has been specially developed for use in all hydraulically operated brake systems for which constructors specify a brake fluid of the type DOT 4+ Low Viscosity. This brake fluid is extremely suitable for brake systems with ESP and ABS systems.

### Complies to the specifications of

FMVSS 116 DOT 4  
ISO 4925 Class 6

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
20500LV	0.5 L	12	-
20001LV	1 L	6	450
20005LV	5 L	4	112
20020LV	20 L	1	30
20060LV	60 L	1	12
20205LV	205 L	1	2
20999LV	1000 L	1	-
P20000LV	1 L	1	-

## Standard analyses

TEST	VALUE	
Density at 20°C	1.06	kg/l
Colour	yellow	
Kinematic Viscosity at 100°C	2.1	mm <sup>2</sup> /s
Kinematic Viscosity at -40°C	650	mm <sup>2</sup> /s
PH	7.5	
Wet Boiling Point	178	°C
Boiling Point	272	°C

These characteristics are typical of current production. Variations in these characteristics may occur.