

## 41000C Motor Oil SAE 30 Single Grade Classic

Document version: 18 Mar 2024



Description

According to the specifications of

Packaging units

This mineral SAE 30 Super Single Grade oil has been developed for a wide range of purposes and is extremely suitable for stationary engines, for industrial transmissions and for hydraulic systems.

API CC / SF CCMC D1 CCMC G2

| ART. NR. | VOLUME | ITEMS PER UNI | T ITEMS PER PALLET |
|----------|--------|---------------|--------------------|
| 41001C   | 1 L    | 6             | 450                |
| 41005C   | 5 L    | 4             | 112                |
| 41020C   | 20 L   | 1             | 30                 |
| 41060C   | 60 L   | 1             | 6                  |
| 41205C   | 205 L  | 1             | 2                  |
| 41999C   | 1000 L | 1             | -                  |
| P41000C  | 1 L    | 1             | -                  |

Standard analyses

| TEST                         | VALUE  |         | METHOD |
|------------------------------|--------|---------|--------|
| Density at 15°C              | 0.891  | kg/l    |        |
| Viscosity                    | SAE 30 |         |        |
| Kinematic Viscosity at 40°C  | 103    | mm2/s   |        |
| Kinematic Viscosity at 100°C | 11.3   | mm2/s   |        |
| Viscosity Index              | 95     |         |        |
| Flashpoint COC               | 240    | °C      |        |
| Pourpoint                    | -21    | °C      |        |
| Total Base Number            | 4.4    | mgKOH/g |        |
| Sulphated Ash                | 0.76   | mass%   |        |

These characteristics are typical of current production. Variations in these characteristics may occur.