

49000 Vacuum Pump Oil ISO VG 100

Document version: Mar 17, 2024

Description

The vacuum pump oil is a mineral oil with anti wear, corrosion, oxidation and foaming additives. This oil is perfectly suitable for the use in vacuum pumps, tool machinery and other hydraulic applications where the requirement ISO VG 100 is. This oil is recommended by brands like Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco, Worthinghton etc.

According to the specifications of

AFNOR NF E 48-603 HM / NF E 48-690 / NF E 48-691 DIN 51524 Part 2 HLP Denison HF-2 Eaton Vickers I-286-S / M-2950-S ISO 11158 HM / 6743-4 HM

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
49020	20 L	1	30
49060	60 L	1	6
49205	205 L	1	2
49999	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C ISO VG Classification	0.877 100	kg/l	
Viscosity Kinematic Viscosity at 40°C	ISO VG 100 101	mm2/s	
Kinematic Viscosity at 100°C	11.4	mm2/s	
Viscosity Index Flashpoint COC	99 232	°C	
Pourpoint Total Acid Number	-24 0.36	°C mgKOH/g	

These characteristics are typical of current production. Variations in these characteristics may occur.