

54000A 4-Stroke Motorcycle Oil 10W-30 Semi Synthetic MB

Document version: 19 Mar 2024



Description

MPM 4-Stroke Motorcycle Oil 10W-30 Synthetic Technology is a special developed engine oil for advanced 4-stroke motor-scooter engines with CVT gearboxes. The high-performance blend gives due to the low friction properties optimal protection under heavy conditions. It allows the engine and CVT gearbox to perform in many different circumstances like city and highway traffic, also required for engines with Start- & Stopsystems.

Note: This oil is not suitable in standard motorcycle engines and transmissions with or without wet clutches.

According to the specifications of

Packaging units

API SJ JASO MB

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER
54001A	1 L	6	450
54020A	20 L	1	30
54060A	60 L	1	6
54205A	205 L	1	2
54999A	1000 L	1	_

PALLET

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.853	kg/l	ASTM D4052
Colour SAE	Amber 10W-30		VISUAL
Kinematic Viscosity at 40°C	73.0	mm2/s	ASTM D445
Kinematic Viscosity at 100°C Viscosity Index	11.2 145	mm2/s	ASTM D445 ASTM D2270
Dynamic Viscosity at -30°C	68000	mPa.s	ASTM D5293
Flashpoint	235	°C	ASTM D92
Pourpoint	-21	°C	ASTM
			D7346

These characteristics are typical of current production. Variations in these characteristics may occur.