



## 05000C2 Motor Oil 5W-30 Premium Synthetic C2

Document version: May 18, 2025



### Description

This Premium Synthetic 'MID SAPS' engine oil has been specially developed for Fiat and Toyota passenger cars and light commercial vehicles, among others. It is also suitable for vehicles requiring SAE 5W-30 with ACEA C2 specifications. With its advanced formula, this oil meets the strict requirements of Euro 4 and Euro 5 petrol and diesel engines, with or without a diesel particulate filter (DPF).

### Application manual

### According to the specifications of

ACEA C2  
API CF / SN  
Fiat 9.55535-S1  
PSA B71 2290 <2017  
Renault RN 0700

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001C2	1 L	6	450
05005C2	5 L	4	112
05020C2	20 L	1	-
05B20C2	20 L	1	-
05060C2	60 L	1	-
05205C2	205 L	1	2
05999C2	1000 L	1	-
P05000C2	1 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density	0.856	kg/l
Viscosity	5W-30	
Kinematic Viscosity	10.1	mm <sup>2</sup> /s
Viscosity Index	170	
Dynamic Viscosity	4700	mPa.s
Flashpoint	214	°C
Pourpoint	-39	°C
Total Base Number	7.9	mgKOH/g
Sulphated Ash	0.8	mass%
High Temperature High Share	3	mPa.s
Noack Evaporation Loss	10.9	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.