



TQX.11002 Triple QX Motor Oil 5W-30 SYNPLUS G

Dokumentversion: 17.10.2026



Beschreibung TRIPLE QX SYNPLUS GM 5W30 SYNTHETIC is designed for engines where the GM-LL-A-025 or GM-LL-B-025 specification is required. It offers high temperature piston deposit control and sludge control.

Spezifikationen ACEA A3/B4
API CF / SN

Leistungsniveau GM LL-A-025 / LL-B-025
MB 229.1

Verpackungseinheiten	ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
	TQX.521776042	1 L	12	-
	TQX.521776041	5 L	4	-
	TQX.521776045	20 L	1	-
	TQX.521776049	60 L	1	-
	TQX.521771776	199 L	1	-

Standardanalyse	TEST	WERT		METHODE
	Dichte bei 15°C	0.855	kg/l	ASTM D4052
	Kinematische Viskosität bei 40°C	69.5	mm ² /s	ASTM D445
	Kinematische Viskosität bei 100°C	11.8	mm ² /s	ASTM D445
	Viskositätsindex	166		ASTM D2270
	Flammpunkt COC	216	°C	ASTM D92
	Pourpoint	-39	°C	ASTM D2892
	Gesamtbasenzahl	10.0	mgKOH/g	ASTM D2896