



TQX.11002 Triple QX Motor Oil 5W-30 SYNPLUS G

Document version: Oct 18, 2026



Description	TRIPLE QX SYNPLUS GM 5W30 SYNTHETIC is designed for engines where the GM-LL-A-025 or GM-LL-B-025 specification is required. It offers high temperature piston deposit control and sludge control.			
According to the specifications of	ACEA A3/B4 API CF / SN GM LL-A-025 / LL-B-025 MB 229.1			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776042	1 L	12	-
	TQX.521776041	5 L	4	-
	TQX.521776045	20 L	1	-
	TQX.521776049	60 L	1	-
	TQX.521771776	199 L	1	-
Standard analyses	TEST	VALUE		METHOD
	Density at 15°C	0.855	kg/l	ASTM D4052
	Kinematic Viscosity at 40°C	69.5	mm2/s	ASTM D445
	Kinematic Viscosity at 100°C	11.8	mm2/s	ASTM D445
	Viscosity Index	166		ASTM D2270
	Flashpoint COC	216	°C	ASTM D92
	Pourpoint	-39	°C	ASTM D2892
	Total Base Number	10.0	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.