TQX.11005 Triple QX Motor Oil 5W-30 SYNPLUS F

Dokumentversion: 17.10.2026

Beschreibung

This TQX SYNPLUS FORD 5W30 synthetic lubricant is based on specially selected very high quality base oils of the latest generation plus an advanced addtive package, with has been specially developed for the requirements of Ford WSS-M2C913- C/D specifications. It is characterised by significantly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications.

Spezifikationen

ACEA A5/B5
API CF / SN
ILSAC GF-5

Leistungsniveau

Fiat 9.55535-G1
Ford WSS-M2C913-C / WSS-M2C913-D
Jaguar/Land Rover STJLR.03.5003
Renault RN 0700
VW 530 36

Verpackungseinheiten

ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
TQX.521776072	1 L	12	-
TQX.521776071	5 L	4	-
TQX.521776165	20 L	1	-
TQX.521776169	60 L	1	6
TQX.521776166	199 L	1	-

Standardanalyse

TEST	WERT		METHODE
Dichte bei 15°C	0.854	kg/l	ASTM D4052
Kinematische Viskosität bei 40°C	63.8	mm2/s	ASTM D445
Kinematische Viskosität bei 100°C	11.0	mm2/s	ASTM D445
Viskositätsindex	166		ASTM D2270
Flammpunkt COC	224	°C	ASTM D92
Pourpoint	-42	°C	ASTM D6892
Gesamtbasenzahl	10.4	mgKOH/g	ASTM D2896

Diese Werte sind typisch für die aktuelle Produktion. Abweichungen dieser Werte können auftreten.