



TQX.11005 Triple QX Motor Oil 5W-30 SYNPLUS F

Document version: Oct 18, 2026



Description This TQX SYNPLUS FORD 5W30 synthetic lubricant is based on specially selected very high quality base oils of the latest generation plus an advanced additive package, with has been specially developed for the requirements of Ford WSS-M2C913- C/D specifications. It is characterised by significantly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications.

According to the specifications of ACEA A5/B5
API CF / SN
Fiat 9.55535-G1
Ford WSS-M2C913-C / WSS-M2C913-D
ILSAC GF-5
Jaguar/Land Rover STJLR.03.5003
Renault RN 0700
VW 530 36

Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776072	1 L	12	-
	TQX.521776071	5 L	4	-
	TQX.521776165	20 L	1	-
	TQX.521776169	60 L	1	6
	TQX.521776166	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.854	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	63.8	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	11.0	mm2/s	ASTM D445
Viscosity Index	166		ASTM D2270
Flashpoint COC	224	°C	ASTM D92
Pourpoint	-42	°C	ASTM D6892
Total Base Number	10.4	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.