



TQX.11005 Triple QX Motor Oil 5W-30 SYNPLUS F

Version du document: 17 oct. 2026



Description

This TQX SYNPLUS FORD 5W30 synthetic lubricant is based on specially selected very high quality base oils of the latest generation plus an advanced additive package, which has been specially developed for the requirements of Ford WSS-M2C913- C/D specifications. It is characterised by significantly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications.

Selon les spécifications de

ACEA A5/B5
API CF / SN
Fiat 9.55535-G1
Ford WSS-M2C913-C / WSS-M2C913-D
ILSAC GF-5
Jaguar/Land Rover STJLR.03.5003
Renault RN 0700
VW 530 36

Unités d'emballage

ART. N°	VOLUME	ARTICLES PAR UNITÉ	ARTICLES PAR PALETTE
TQX.521776072	1 L	12	-
TQX.521776071	5 L	4	-
TQX.521776165	20 L	1	-
TQX.521776169	60 L	1	6
TQX.521776166	199 L	1	-

Analyses standard

TEST	VALEUR		METHOD
Densité à 15 °Celsius	0.854	kg/l	ASTM D4052
Viscosité cinématique à 40 °Celsius	63.8	mm2/s	ASTM D445
Viscosité cinématique à 100 °Celsius	11.0	mm2/s	ASTM D445
Indice de viscosité	166		ASTM D2270
Point d'éclair COC	224	°C	ASTM D92
Point d'écoulement	-42	°C	ASTM D6892
Indice de basicité totale	10.4	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.