



TQX.11005 Triple QX Motor Oil 5W-30 SYNPLUS F

Documentversie: 18 okt. 2026



Omschrijving

This TQX SYNPLUS FORD 5W30 synthetic lubricant is based on specially selected very high quality base oils of the latest generation plus an advanced additive package, with has been specially developed for the requirements of Ford WSS-M2C913- C/D specifications. It is characterised by significantly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications.

Volgens de specificaties van

ACEA A5/B5
API CF / SN
Fiat 9.55535-G1
Ford WSS-M2C913-C / WSS-M2C913-D
ILSAC GF-5
Jaguar/Land Rover STJLR.03.5003
Renault RN 0700
VW 530 36

Verpakkingseenheden

ART. NR.	VOLUME	AANTAL PER STUK	AANTAL PER PALLET
TQX.521776072	1 L	12	-
TQX.521776071	5 L	4	-
TQX.521776165	20 L	1	-
TQX.521776169	60 L	1	6
TQX.521776166	199 L	1	-

Standaardanalyses

TEST	WAARDE		METHODE
Dichtheid bij 15°C	0.854	kg/l	ASTM D4052
Kinematische viscositeit bij 40°C	63.8	mm ² /s	ASTM D445
Kinematische viscositeit bij 100°C	11.0	mm ² /s	ASTM D445
Viscositeitsindex	166		ASTM D2270
Vlampunt COC	224	°C	ASTM D92
Vloeipunt	-42	°C	ASTM D6892
Totaal Base-getal	10.4	mgKOH/g	ASTM D2896

Deze waarden zijn typerend voor de huidige productie. Er kan variatie in de waarden optreden.