



TQX.11006 Triple QX Motor Oil 5W-40 SYNPLUS C3

Document version: Oct 18, 2026



Description

TRIPLE QX SYNPLUS PD 5W40 SYNTHETIC is a premium synthetic lubricant engineered to meet the stringent requirements of the VW 505.01 specification, delivering outstanding resistance to oxidation, oil thickening, and sludge formation. This mid-SAPS formulation ensures dependable protection for after-treatment exhaust systems, including Diesel Particulate Filters

According to the specifications of

ACEA C3
API CF / SN
BMW Longlife-04
Ford WSS-M2C917-A
GM dexos 2
MB 229.31 / 229.51
Porsche A40
Renault RN 0700 / RN 0710
VW 505.00 / 505.01

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776082	1 L	12	-
TQX.521776081	5 L	4	-
TQX.521776085	20 L	1	-
TQX.521776089	60 L	1	-
TQX.521772036	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.849	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	80.5	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	13.8	mm2/s	ASTM D445
Viscosity Index	177		ASTM D2270
Pourpoint	-42	°C	ASTM D6892
Total Base Number	6.8	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.