



TQX.11008 Triple QX Motor Oil 0W-30 SYNPLUS

Dokumentversion: 17.10.2026



Beschreibung

This TQX SYNPLUS 0W30 synthetic lubricant is based on carefully selected very high quality base oils that was especially developed to meet the ACEA A5/B5 requirements. It is characterized by increased lubricating properties and a better fuel economy. In this way it procures a reduced fuel consumption and a longer lifetime of the engine.

Anwendungshandbuch

This oil is recommended for the four stroke gasoline and diesel models of Volvo Cars of the latest generations, equipped with 5-cylinder engines and Volkswagen where the specification 503.00/ 506.00 or 506.01 is required. Never use in VW engines where VW specification 503.01 is required.

Spezifikationen

ACEA A5/B5
API CF / SN
ILSAC GF-5

Leistungsniveau

Renault RN 0700
VW 503.00 / 506.00 / 506.01
Volvo VCC 95200377

Verpackungseinheiten

ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
TQX.521776142	1 L	12	-
TQX.521776141	5 L	4	-
TQX.521776145	20 L	1	-
TQX.521771046	199 L	1	-

Standardanalyse

TEST	WERT		METHODE
Dichte bei 15°C	0.844	kg/l	ASTM D4052
Kinematische Viskosität bei 40°C	53.2	mm ² /s	ASTM D445
Kinematische Viskosität bei 100°C	10.0	mm ² /s	ASTM D445
Viskositätsindex	180		ASTM D2270
Flammpunkt COC	225	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Gesamtbasenzahl	10.3	mgKOH/g	ASTM D2896
Sulfatasche	1.09	mass%	ASTM D874

Diese Werte sind typisch für die aktuelle Produktion. Abweichungen dieser Werte können auftreten.