



TQX.11009 Triple QX Motor Oil 0W-20 SYNPLUS

Document version: Oct 18, 2026



Description

TRIPLE QX SYNPLUS 0W-20 SYNTHETIC is based on carefully selected very high quality base oils, offering the highest levels of fuel economy in passenger cars. Due to its carefully selected base oils and premium additives, it is designed to deliver outstanding engine protection against wear and deposits. Its exceptionally low viscosity allows it to be used the year round, also during very low temperatures in the wintertime. This product is specifically designed to offer fuel economy benefits.

Application manual

This product has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen 3 specification and ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

According to the specifications of

API SN Plus / SN-RC / SP / SP-RC
Chrysler MS-6395
Fiat 9.55535-CR1
Ford M2C947-A / M2C962-A1
GM dexos1 Gen 3
ILSAC GF-5 / GF-6A

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776262	1 L	12	-
TQX.521776261	5 L	4	-
TQX.521776265	20 L	1	-
TQX.521776266	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.847	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	45.6	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	8.53	mm2/s	ASTM D445
Viscosity Index	167		ASTM D2270
Flashpoint	220	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	7.4	mgKOH/g	ASTM D2896
Sulphated Ash	0.79	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.