



TQX.11011 Triple QX Motor Oil 5W-30 SYNPLUS C1

Dokumentversion: 17.10.2026



Beschreibung TRIPLE QX SYNPLUS C1 5W-30 SYNTHETIC is a high performance synthetic lubricant formulated with carefully selected, premiumquality base oils. This LOW SAPS oil is designed for gasoline, LPG, and diesel passenger car engines—both turbocharged and naturally aspirated—that require minimal levels of sulphated ash, phosphorus, and sulfur. It delivers excellent fuel economy while ensuring optimal protection and performance.

Anwendungshandbuch This oil is specifically designed for the newest generation (Euro 4) gasoline and diesel passengercar engines with diesel particulate filters (DPF), which require a low HTHS viscosity oil. It procures a significant improvement in fuel economy. This engine oil can also be used, where ILSAC GF-4 oils are recommended.

Spezifikationen ACEA C1
JASO DL-1

Leistungsniveau Ford M2C934-B
Jaguar/Land Rover STJLR.03.5005

Verpackungseinheiten	ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
	TQX.521776222	1 L	12	-
	TQX.521776221	5 L	4	-
	TQX.521776225	20 L	1	-
	TQX.521776226	199 L	1	-

Standardanalyse

TEST	WERT		METHODE
Dichte bei 15°C	0.852	kg/l	ASTM D4052
CCS bei -30°C	5600	mPa·s	ASTM D5293
Kinematische Viskosität bei 40°C	59.1	mm ² /s	ASTM D445
Kinematische Viskosität bei 100°C	10.5	mm ² /s	ASTM D445
Viskositätsindex	169		ASTM D2270
Flammpunkt COC	224	°C	ASTM D92
Pourpoint	-45	°C	ASTM D6892
Gesamtbasenzahl	6.4	mgKOH/g	ASTM D2896
Sulfatasche	0.5	mass%	ASTM D874

Diese Werte sind typisch für die aktuelle Produktion. Abweichungen dieser Werte können auftreten.