



TQX.11011 Triple QX Motor Oil 5W-30 SYNPLUS C1

Document version: Oct 18, 2026



Description	TRIPLE QX SYNPLUS C1 5W-30 SYNTHETIC is a high performance synthetic lubricant formulated with carefully selected, premiumquality base oils. This LOW SAPS oil is designed for gasoline, LPG, and diesel passenger car engines—both turbocharged and naturally aspirated—that require minimal levels of sulphated ash, phosphorus, and sulfur. It delivers excellent fuel economy while ensuring optimal protection and performance.			
Application manual	This oil is specifically designed for the newest generation (Euro 4) gasoline and diesel passengercar engines with diesel particulate filters (DPF), which require a low HTHS viscosity oil. It procures a significant improvement in fuel economy. This engine oil can also be used, where ILSAC GF-4 oils are recommended.			
According to the specifications of	ACEA C1 Ford M2C934-B JASO DL-1 Jaguar/Land Rover STJLR.03.5005			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776222	1 L	12	-
	TQX.521776221	5 L	4	-
	TQX.521776225	20 L	1	-
	TQX.521776226	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.852	kg/l	ASTM D4052
CCS at -30°C	5600	mPa·s	ASTM D5293
Kinematic Viscosity at 40°C	59.1	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	10.5	mm2/s	ASTM D445
Viscosity Index	169		ASTM D2270
Flashpoint COC	224	°C	ASTM D92
Pourpoint	-45	°C	ASTM D6892
Total Base Number	6.4	mgKOH/g	ASTM D2896
Sulphated Ash	0.5	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.