



TQX.11012 Triple QX Motor Oil 5W-20 SYNPLUS EB

Dokumentversion: 17.10.2026



Beschreibung

TRIPLE QX SYNPLUS ECOBOOST 5W-20 SYNTHETIC is based on carefully selected very high quality base oils. This oil is extremely fuel-efficient and meets the requirements of the new Ford EcoBoost petrol engines. It ensures a reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission. It has excellent cold starting behavior giving a very good operating reliability.

Anwendungshandbuch

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA C5 or API SN.

Spezifikationen

ACEA C5
API SN-RC
ILSAC GF-5

Leistungsniveau

Chrysler MS-6395
Ford WSS-M2C948-A / WSS-M2C948-B
Jaguar/Land Rover STJLR.03.5004

Verpackungseinheiten

ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
TQX.521776212	1 L	12	-
TQX.521776211	5 L	4	-
TQX.521776215	20 L	1	-
TQX.521776216	199 L	1	-

Standardanalyse

TEST	WERT		METHODE
Dichte bei 15°C	0.851	kg/l	ASTM D4052
CCS bei -30°C	5500	mPa·s	ASTM D5293
Kinematische Viskosität bei 40°C	42.3	mm ² /s	ASTM D445
Kinematische Viskosität bei 100°C	7.9	mm ² /s	ASTM D445
Viskositätsindex	162		ASTM D2270
Flammpunkt COC	220	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Gesamtbasenzahl	7.6	mgKOH/g	ASTM D2896
Sulfatasche	0.8	mass%	ASTM D874

Diese Werte sind typisch für die aktuelle Produktion. Abweichungen dieser Werte können auftreten.