



TQX.11012 Triple QX Motor Oil 5W-20 SYNPLUS EB

Document version: Oct 18, 2026



Description

TRIPLE QX SYNPLUS ECOBOOST 5W-20 SYNTHETIC is based on carefully selected very high quality base oils. This oil is extremely fuel-efficient and meets the requirements of the new Ford EcoBoost petrol engines. It ensures a reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission. It has excellent cold starting behavior giving a very good operating reliability.

Application manual

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA C5 or API SN.

According to the specifications of

ACEA C5
API SN-RC
Chrysler MS-6395
Ford WSS-M2C948-A / WSS-M2C948-B
ILSAC GF-5
Jaguar/Land Rover STJLR.03.5004

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776212	1 L	12	-
TQX.521776211	5 L	4	-
TQX.521776215	20 L	1	-
TQX.521776216	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.851	kg/l	ASTM D4052
CCS at -30°C	5500	mPa·s	ASTM D5293
Kinematic Viscosity at 40°C	42.3	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	7.9	mm ² /s	ASTM D445
Viscosity Index	162		ASTM D2270
Flashpoint COC	220	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	7.6	mgKOH/g	ASTM D2896
Sulphated Ash	0.8	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.