



TQX.11014 Triple QX Motor Oil 0W-40 SYNPLUS

Dokumentversion: 17.10.2026



Beschreibung	Triple QX Motor Oil 0W-40 SYNPLUS is a synthetic lubricant based on carefully selected very high quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.			
Anwendungshandbuch	All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.			
Spezifikationen	ACEA A3/B4 API CF / SN			
Leistungsniveau	BMW Longlife-01 Ford M2C937-A MB 226.5 / 229.5 Porsche A40 Renault RN 0700 / RN 0710 VW 502.00 / 505.00			
Verpackungseinheiten	ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
	TQX.521776272	1 L	12	-
	TQX.521776271	5 L	4	-
	TQX.521776275	20 L	1	-
	TQX.521776276	199 L	1	-

Standardanalyse

TEST	WERT		METHODE
Dichte bei 15°C	0.846	kg/l	ASTM D4052
Kinematische Viskosität bei 40°C	78.0	mm ² /s	ASTM D445
Kinematische Viskosität bei 100°C	13.8	mm ² /s	ASTM D445
Viskositätsindex	183		ASTM D2270
Flammpunkt COC	222	°C	ASTM D92
Pourpoint	-42	°C	ASTM D6892
Gesamtbasenzahl	10.4	mgKOH/g	ASTM D2896
Sulfatasche	1.36	mass%	ASTM D874

Diese Werte sind typisch für die aktuelle Produktion. Abweichungen dieser Werte können auftreten.