



TQX.11014 Triple QX Motor Oil 0W-40 SYNPLUS

Document version: Oct 18, 2026



Description	Triple QX Motor Oil 0W-40 SYNPLUS is a synthetic lubricant based on carefully selected very high quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.			
Application manual	All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.			
According to the specifications of	ACEA A3/B4 API CF / SN BMW Longlife-01 Ford M2C937-A MB 226.5 / 229.5 Porsche A40 Renault RN 0700 / RN 0710 VW 502.00 / 505.00			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776272	1 L	12	-
	TQX.521776271	5 L	4	-
	TQX.521776275	20 L	1	-
	TQX.521776276	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.846	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	78.0	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	13.8	mm2/s	ASTM D445
Viscosity Index	183		ASTM D2270
Flashpoint COC	222	°C	ASTM D92
Pourpoint	-42	°C	ASTM D6892
Total Base Number	10.4	mgKOH/g	ASTM D2896
Sulphated Ash	1.36	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.