



TQX.11014 Triple QX Motor Oil 0W-40 SYNPLUS

Version du document: 17 oct. 2026



Description

Triple QX Motor Oil 0W-40 SYNPLUS is a synthetic lubricant based on carefully selected very high quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.

Manuel d'application

All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.

Selon les spécifications de

ACEA A3/B4
API CF / SN
BMW Longlife-01
Ford M2C937-A
MB 226.5 / 229.5
Porsche A40
Renault RN 0700 / RN 0710
VW 502.00 / 505.00

Unités d'emballage

ART. N°	VOLUME	ARTICLES PAR UNITÉ	ARTICLES PAR PALETTE
TQX.521776272	1 L	12	-
TQX.521776271	5 L	4	-
TQX.521776275	20 L	1	-
TQX.521776276	199 L	1	-

Analyses standard

TEST	VALEUR		METHOD
Densité à 15 °Celsius	0.846	kg/l	ASTM D4052
Viscosité cinématique à 40 °Celsius	78.0	mm ² /s	ASTM D445
Viscosité cinématique à 100 °Celsius	13.8	mm ² /s	ASTM D445
Indice de viscosité	183		ASTM D2270
Point d'éclair COC	222	°C	ASTM D92
Point d'écoulement	-42	°C	ASTM D6892
Indice de basicité totale	10.4	mgKOH/g	ASTM D2896
Cendres sulfatées	1.36	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.