



TQX.11014 Triple QX Motor Oil 0W-40 SYNPLUS

Documentversie: 18 okt. 2026



Omschrijving

Triple QX Motor Oil 0W-40 SYNPLUS is a synthetic lubricant based on carefully selected very high quality base oils of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.

Toepassingshandleiding

All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.

Volgens de specificaties van

ACEA A3/B4
API CF / SN
BMW Longlife-01
Ford M2C937-A
MB 226.5 / 229.5
Porsche A40
Renault RN 0700 / RN 0710
VW 502.00 / 505.00

Verpakkingseenheden

ART. NR.	VOLUME	AANTAL PER STUK	AANTAL PER PALLET
TQX.521776272	1 L	12	-
TQX.521776271	5 L	4	-
TQX.521776275	20 L	1	-
TQX.521776276	199 L	1	-

Standaardanalyses

TEST	WAARDE		METHODE
Dichtheid bij 15°C	0.846	kg/l	ASTM D4052
Kinematische viscositeit bij 40°C	78.0	mm ² /s	ASTM D445
Kinematische viscositeit bij 100°C	13.8	mm ² /s	ASTM D445
Viscositeitsindex	183		ASTM D2270
Vlampunt COC	222	°C	ASTM D92
Vloeipunt	-42	°C	ASTM D6892
Totaal Base-getal	10.4	mgKOH/g	ASTM D2896
Sulfaatas	1.36	mass%	ASTM D874

Deze waarden zijn typerend voor de huidige productie. Er kan variatie in de waarden optreden.