



TQX.11015 Triple QX Motor Oil 0W-20 SYNPLUS LL
IV

Dokumentversion: 17.10.2026



Beschreibung	TQX SYNPLUS VAG FS 0W20 is a synthetic lubricant mandatory for the newest engines of VW/Audi. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep your engine running like new. A substantial fuel saving is reached through the use of the ultra-low 0W20 viscosity grade.			
Spezifikationen	ACEA C5, C6 API SN			
Leistungsniveau	Ford WSS-M2C956-A1 Porsche C20 VW 508.00 / 509.00			
Verpackungseinheiten	ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
	TQX.521773542	1 L	12	-
	TQX.521773541	5 L	4	-
	TQX.521773545	20 L	1	-
	TQX.521773549	60 L	1	6
	TQX.521773546	199 L	1	-

Standardanalyse

TEST	WERT		METHODE
Dichte bei 15°C	0.847	kg/l	ASTM D4052
Farbe	Green		Visual
Kinematische Viskosität bei 40°C	42.0	mm ² /s	ASTM D445
Kinematische Viskosität bei 100°C	8.1	mm ² /s	ASTM D445
Viskositätsindex	170		ASTM D2270
Pourpoint	-48	°C	ASTM D6892
Gesamtbasenzahl	8.9	mgKOH/g	ASTM D2896
Sulfatasche	0.79	mass%	ASTM D874

Diese Werte sind typisch für die aktuelle Produktion. Abweichungen dieser Werte können auftreten.