



TQX.11015 Triple QX Motor Oil 0W-20 SYNPLUS LL
IV

Document version: Oct 18, 2026



Description	TQX SYNPLUS VAG FS 0W20 is a synthetic lubricant mandatory for the newest engines of VW/Audi. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep your engine running like new. A substantial fuel saving is reached through the use of the ultra-low 0W20 viscosity grade.			
According to the specifications of	ACEA C5, C6 API SN Ford WSS-M2C956-A1 Porsche C20 VW 508.00 / 509.00			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521773542	1 L	12	-
	TQX.521773541	5 L	4	-
	TQX.521773545	20 L	1	-
	TQX.521773549	60 L	1	6
	TQX.521773546	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.847	kg/l	ASTM D4052
Colour	Green		Visual
Kinematic Viscosity at 40°C	42.0	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	8.1	mm2/s	ASTM D445
Viscosity Index	170		ASTM D2270
Pourpoint	-48	°C	ASTM D6892
Total Base Number	8.9	mgKOH/g	ASTM D2896
Sulphated Ash	0.79	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.