



TQX.11017 Triple QX Motor Oil 0W-30 SYNPLUS F

Dokumentversion: 17.10.2026



Beschreibung

This TQX SYNPLUS FORD FS 0W30 is a fuel saving synthetic lubricant based on carefully selected base oils, mandatory for the EURO 6 TDCI Duratorq engines of the most recent Ford models (> 2014) with exhaust after treatment and turbocharger. The high-tech VI-improver provides high stability to ensure long oil drain intervals. It also addresses the use of biofuels, has special elastomer compatibility and anti-wear chain characteristics.

Anwendungshandbuch

This product is developed for mandatory use in the newest EURO 6 TDCI Duratorq Ford engines. This product is also usable for other passenger car engines requiring a 0W-30 viscosity grade and the ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for today's car engines with exceptional fuel economy and extended service intervals.

Spezifikationen

ACEA C2
API SN
ILSAC GF-5

Leistungsniveau

Ford WSS-M2C950-A
Jaguar/Land Rover STJLR.03.5007
VW 530 35

Verpackungseinheiten

ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
TQX.521773652	1 L	12	-
TQX.521773651	5 L	4	-
TQX.521773655	20 L	1	-
TQX.521773656	199 L	1	-

Standardanalyse

TEST	WERT		METHODE
Dichte bei 15°C	0.845	kg/l	ASTM D4052
Kinematische Viskosität bei 40°C	54	mm ² /s	ASTM D445
Kinematische Viskosität bei 100°C	10.2	mm ² /s	ASTM D445
Viskositätsindex	180		ASTM D2270
Pourpoint	-42	°C	ASTM D6892
Gesamtbasenzahl	7.2	mgKOH/g	ASTM D2896
Sulfatasche	0.79	mass%	ASTM D874
Brookfield-Viskosität bei -35°C	5600	mPa.s	ASTM D5293

Diese Werte sind typisch für die aktuelle Produktion. Abweichungen dieser Werte können auftreten.