



TQX.11017 Triple QX Motor Oil 0W-30 SYNPLUS F

Document version: Oct 18, 2026



Description	This TQX SYNPLUS FORD FS 0W30 is a fuel saving synthetic lubricant based on carefully selected base oils, mandatory for the EURO 6 TDCI Duratorq engines of the most recent Ford models (> 2014) with exhaust after treatment and turbocharger. The high-tech VI-improver provides high stability to ensure long oil drain intervals. It also addresses the use of biofuels, has special elastomer compatibility and anti-wear chain characteristics.			
Application manual	This product is developed for mandatory use in the newest EURO 6 TDCI Duratorq Ford engines. This product is also usable for other passenger car engines requiring a 0W-30 viscosity grade and the ACEA C2 performance, thus providing a multi vehicle oil application. Optimum formulation for today's car engines with exceptional fuel economy and extended service intervals.			
According to the specifications of	ACEA C2 API SN Ford WSS-M2C950-A ILSAC GF-5 Jaguar/Land Rover STJLR.03.5007 VW 530 35			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521773652	1 L	12	-
	TQX.521773651	5 L	4	-
	TQX.521773655	20 L	1	-
	TQX.521773656	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.845	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	54	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	10.2	mm2/s	ASTM D445
Viscosity Index	180		ASTM D2270
Pourpoint	-42	°C	ASTM D6892
Total Base Number	7.2	mgKOH/g	ASTM D2896
Sulphated Ash	0.79	mass%	ASTM D874
Brookfield Viscosity at -35°C	5600	mPa.s	ASTM D5293

These characteristics are typical of current production. Variations in these characteristics may occur.