



TQX.11019 Triple QX Motor Oil 0W-30 SYNPLUS C2

Document version: Oct 18, 2026



Description

This TRIPLE QX SYNPLUS PSA C2 0W-30 synthetic lubricant is for petrol and diesel engines equipped with an exhaust after-treatment system. Suitable for an extended drain interval even with the use of bio-components in the fuel. Excellent viscosity at low temperatures in combination with the stop / start technologies. This engine oil is suitable for various Peugeot, Citroën and Fiat engines. Also usable for other passenger cars requiring a 0W-30 viscosity grade and ACEA C2 performance.

According to the specifications of

ACEA C2
Fiat 9.55535-DS1 / 9.55535-GS1
PSA B71 2312

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521773952	1 L	12	-
TQX.521773951	5 L	4	-
TQX.521773955	20 L	1	-
TQX.521773959	60 L	1	6
TQX.521773956	199 L	1	-

Standard analyses	TEST	VALUE		METHOD
	Density	0.844	kg/l	ASTM D4052
	CCS at -35°C	5950	mPa·s	ASTM D5293
	SAE	0W-30		
	Kinematic Viscosity at 40°C	50.1	mm ² /s	ASTM D445
	Kinematic Viscosity at 100°C	9.6	mm ² /s	ASTM D445
	Viscosity Index	180		ASTM D2270
	Flashpoint COC	226	°C	ASTM D92
	Pourpoint	-42	°C	ASTM D6892
	Sulphated Ash	0.56	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.