



TQX.11020 Triple QX Motor Oil 5W-30 SYNPLUS C2-C3

Document version: Oct 18, 2026

Description This TRIPLE QX SYNPLUS C2-C3 5W-30 synthetic lubricant is designed for petrol en diesel engines where the specification ACEA C2/C3 or API SN/CF is required. The combination of excellent low viscosity properties and highly protective additives enable the engine to run with higher fuel efficiency.

Application manual

According to the specifications of ACEA C2 / C3
API CF / SN

Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776925	20 L	1	-
	TQX.521776926	199 L	1	-

Standard analyses	TEST	VALUE		METHOD
	Density at 15°C	0.850	kg/l	ASTM D4052
	Kinematic Viscosity at 40°C	68	mm ² /s	ASTM D445
	Kinematic Viscosity at 100°C	11.8	mm ² /s	ASTM D445
	Viscosity Index	171		ASTM D2270
	Flashpoint	230	°C	ASTM D92
	Total Base Number	6.8	mgKOH/g	ASTM D2896
	Sulphated Ash	0.787	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.