



TQX.11021 Triple QX Motor Oil 0W-20 SYNPLUS
C5-C6

Document version: Oct 18, 2026



Application manual

Triple QX Motor Oil 0W-20 SYNPLUS C5-C6 is a synthetic engine oil developed for modern gasoline and diesel engines in passenger cars and light commercial vehicles. Its ultra-low viscosity enhances fuel efficiency and reduces emissions while maintaining outstanding engine protection. Advanced additive technology keeps the engine clean, prevents harmful deposits and provides excellent wear protection. The formulation ensures rapid lubrication during cold starts and reliable performance under demanding conditions. Suitable for modern engines equipped with aftertreatment systems, GDI technology and hybrid applications (when prescribed by the manufacturer). Also compatible with the latest fuel types, including biofuels and ethanol blends.

According to the specifications of

- ACEA C5, C6
- API SP / SP-RC / SQ / SQ-RC
- BMW LL-17FE+
- Fiat 9.55535-DM1 / 9.55535-DSX
- GM Dexos D
- ILSAC GF-6A / GF-7A
- Jaguar/Land Rover STJLR.03.5006 / STJLR.51.5122
- MB 229.71 / 229.72
- Opel OV 040 1547 - A20
- Volvo VCC RBS0-2AE

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776252	1 L	12	-
TQX.521776251	5 L	4	-
TQX.521776255	20 L	1	-
TQX.521776256	199 L	1	-

Standard analyses	TEST	VALUE		METHOD
	Density	0.847	kg/l	ASTM D4052
	Kinematic Viscosity at 40°C	42.1	mm2/s	ASTM D445
	Kinematic Viscosity at 100°C	8.1	mm2/s	ASTM D445
	Viscosity Index	170		ASTM D2270
	Flashpoint	210	°C	ASTM D92
	Pourpoint	-39	°C	ASTM D6892

These characteristics are typical of current production. Variations in these characteristics may occur.