



TQX.13002 Triple QX Motor Oil 5W-30 SEMI
SYNPLUS

Document version: Oct 18, 2026



Description	TRIPLE QX PREMIUM 5W-30 SEMI SYNTHETIC is formulated with specially selected, high quality base oils and a modern additive package. Its advanced composition, including a friction modifier, helps deliver noticeable fuel savings. Excellent low-temperature fluidity ensures minimal resistance during cold starts, effectively reducing engine wear to a minimum			
Application manual	All modern four-stroke gasoline- and diesel car engines without particle filters where ACEA A5/B5 level is required.			
According to the specifications of	ACEA A5/B5 API CF / SL / SN Ford WSS-M2C913-A / WSS-M2C913-B ILSAC GF-5			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776022	1 L	12	-
	TQX.521776021	5 L	4	-
	TQX.521776025	20 L	1	-
	TQX.521771636	199 L	1	-

Standard analyses	TEST	VALUE		METHOD
	Density at 15°C	0.854	kg/l	ASTM D4052
	CCS at -30°C	6000	mPa·s	ASTM D5293
	Kinematic Viscosity at 40°C	60.0	mm2/s	ASTM D445
	Kinematic Viscosity at 100°C	10.2	mm2/s	ASTM D445
	Viscosity Index	158		ASTM D2270
	Flashpoint COC	214	°C	ASTM D92
	Pourpoint	-39	°C	ASTM D6892
	Total Base Number	8.2	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.