



TQX.132004 Triple QX Antifreeze Concentrated Purple G12evo

Documentversie: 23 okt. 2026



Omschrijving

This High Quality Antifreeze is silicate containing, incorporating the latest in Organic Acid Technology (OAT). Suitable for all engine types conforming to G13 standards. Colour: purple Protection: Mix 50% Antifreeze - 50% Water Up to -36°C Mix 33% Antifreeze - 67% Water Up to -20°C It can be left in the system as a coolant and rust inhibitor for up to a maximum of 5 years in accordance with vehicle manufacturer's requirements.

Toepassingshandleiding

Kristallisatiepunt 33 vol % verdund -18°C Kristallisatiepunt 50 vol % verdund -38°C
Kristallisatiepunt 60 vol % verdund -50°C

Volgens de specificaties van

AFNOR NF R 15-601
BS 6580
VW TL 774L G12evo
VW TL 774C G11 / 774D/F G12+ / 774G G12++ / 774J G13

Verpakkingseenheden

ART. NR.	VOLUME	AANTAL PER STUK	AANTAL PER PALLET
TQX.523770492	1 L	12	-
TQX.523770491	5 L	4	-
TQX.52377049T	20 L	1	-
TQX.523770496	199 L	1	-

Standaardanalyses

TEST	WAARDE		METHODE
Dichtheid bij 20°C	1.121	kg/l	ASTM D4052
Kleur	Purple		
Vriespunt 50% verdund	-40	°C	ASTM D1177
Kookpunt	170	°C	ASTM D1120
pH 50% verdund	7.5 - 8.5		ASTM D1287
Water	5	mass%	

Deze waarden zijn typerend voor de huidige productie. Er kan variatie in de waarden optreden.