



TQX.14001 Triple QX Motor Oil 20W-50 MINERAL

Document version: Oct 18, 2026



Description

TRIPLE QX PREMIUM 20W-50 MINERAL is a high quality mineral engine oil suitable for four-stroke gasoline and diesel cars, as well as light commercial vehicles. Its carefully balanced formulation provides excellent oxidation resistance, along with optimal detergent and dispersant properties. A strong oil film ensures excellent lubricating performance and reliable engine protection

Application manual

This oil can be applied in modern 4-stroke gasoline (multi valves, turbo, etc.) and 4-stroke diesel engines, with or without turbo. Also used in classic car engines.

According to the specifications of

ACEA A3/B4
API CF / SN
MB 229.1
PSA B71 2295
VW 501.01 / 505.00

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.521776242	1 L	12	-
TQX.521776241	5 L	4	-
TQX.521776245	20 L	1	-
TQX.521776246	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.892	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	167.0	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	18.3	mm2/s	ASTM D445
Viscosity Index	122		ASTM D2270
Flashpoint COC	222	°C	ASTM D92
Pourpoint	-27	°C	ASTM D6892
Total Base Number	10.2	mgKOH/g	ASTM D2896
Sulphated Ash	1.03	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.