



TQX.22002 Triple QX Motor Oil 15W-40 MINERAL
UHPD

Document version: Oct 18, 2026



Description	TQX ULTRA Diesel 15W40 is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).			
According to the specifications of	ACEA A3/B4 / E7 API CI-4 / SL Caterpillar ECF-1-a / ECF-2 Cummins CES 20077 / CES 20078 Detroit Diesel 93K215 Deutz DQC III-10 Global DHD-1 JASO DH-1 MAN 3275-1 MB 228.3 MTU Oil Category 2 Mack EO-M Plus / EO-N Renault RLD-2 Volvo VDS-3			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776112	1 L	12	-
	TQX.521776111	5 L	4	-
	TQX.521776115	20 L	1	-
	TQX.521772116	199 L	1	-

Standard analyses	TEST	VALUE		METHOD
	Density at 15°C	0.883	kg/l	ASTM D4052
	Kinematic Viscosity at 40°C	99.7	mm2/s	ASTM D445
	Kinematic Viscosity at 100°C	13.6	mm2/s	ASTM D445
	Viscosity Index	136		ASTM D2270
	Pourpoint	-32	°C	ASTM D6892
	Total Base Number	9.2	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.