



TQX.30002 Triple QX Gear Oil 75W-90 SYNPLUS
TDL

Document version: Oct 18, 2026



Description	Excellent resistance against oxidation. Provides good clutch-switch performance at low temperatures.			
According to the specifications of	API GL-3 / GL-4 / GL-5 Arvin Meritor 0-76-N DAF MAN 342 Type M-2 MB 235.0 / 235.8 MIL-L-2105D Mack GO-J Renault Scania STO 1:0 VW G 052 145 / 052 911 Volvo 97312 ZF TE-ML 05A / 07A / 16B / 16D / 17B / 19B / 21A			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.522776022	1 L	12	-
	TQX.522776021	5 L	4	-
	TQX.522776025	20 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.869	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	78	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	14.8	mm2/s	ASTM D445
Viscosity Index	200		
Pourpoint	-42	°C	ASTM D6892
Brookfield Viscosity at -40°C	100000	mPa.s	ASTM D2983

These characteristics are typical of current production. Variations in these characteristics may occur.