



TQX.30003 Triple QX Gear Oil 80W-90 MINERAL

Document version: Oct 18, 2026



Description

Excellent resistance against oxidation. Best used for hypoid differentials. Can be used in transmissions that require EP (extreme pressure) transmission oils

According to the specifications of

API GL-5
DAF
DTFR 12B100
MAN 342 Type M-2
MB 235.0
MIL-L-2105D
Renault
Voith
Volvo 97316
ZF TE-ML 05A / 07A / 12E / 16B / 17B / 19B / 21A

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
TQX.522776032	1 L	12	-
TQX.522776031	5 L	4	-
TQX.522776035	20 L	1	-
TQX.522771066	199 L	1	-

Standard analyses	TEST	VALUE		METHOD
	Density at 15°C	0.893	kg/l	ASTM D4052
	Kinematic Viscosity at 40°C	144	mm2/s	ASTM D445
	Kinematic Viscosity at 100°C	14.2	mm2/s	ASTM D445
	Viscosity Index	103		ASTM D2270
	Flashpoint	210	°C	ASTM D92
	Pourpoint	-33	°C	ASTM D6892
	Brookfield Viscosity at -26°C	120000	mPa.s	ASTM D2983

These characteristics are typical of current production. Variations in these characteristics may occur.