



TQX.30003 Triple QX Gear Oil 80W-90 MINERAL

Documentversie: 18 okt. 2026



Omschrijving Excellent resistance against oxidation. Best used for hypoid differentials. Can be used in transmissions that require EP (extreme pressure) transmission oils

Volgens de specificaties van API GL-5
DAF
DTFR 12B100
MAN 342 Type M-2
MB 235.0
MIL-L-2105D
Renault
Voith
Volvo 97316
ZF TE-ML 05A / 07A / 12E / 16B / 17B / 19B / 21A

Verpakkingseenheden	ART. NR.	VOLUME	AANTAL PER STUK	AANTAL PER PALLET
	TQX.522776032	1 L	12	-
	TQX.522776031	5 L	4	-
	TQX.522776035	20 L	1	-
	TQX.522771066	199 L	1	-

Standaardanalyses	TEST	WAARDE		METHODE
	Dichtheid bij 15°C	0.893	kg/l	ASTM D4052
	Kinematische viscositeit bij 40°C	144	mm ² /s	ASTM D445
	Kinematische viscositeit bij 100°C	14.2	mm ² /s	ASTM D445
	Viscositeitsindex	103		ASTM D2270
	Vlampunt	210	°C	ASTM D92
	Vloeipunt	-33	°C	ASTM D6892
	Brookfield-viscositeit bij 20°C	120000	mPa.s	ASTM D2983