



TQX.30006 Triple QX Gear Oil 75W-90 SEMI SYNPLUS

Document version: Oct 18, 2026



Description Suitable for use in manual gearboxes and hypoid rear axles. Can be used in applications where EP (extreme pressure) gear oils are recommended.

According to the specifications of

API GL-5
DAF
DTFR 12B100
MAN 342 Type M-2
MB 235.0
MIL-L-2105D
Renault
Volvo
ZF TE-ML 05A / 07A / 12E / 16B / 17B / 19B / 21A

Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.522776112	1 L	12	-
	TQX.522776111	5 L	4	-
	TQX.522776115	20 L	1	-
	TQX.522771056	199 L	1	-

Standard analyses	TEST	VALUE		METHOD
	Density at 15°C	0.861	kg/l	ASTM D4052
	Kinematic Viscosity at 40°C	81	mm ² /s	ASTM D445
	Kinematic Viscosity at 100°C	14.8	mm ² /s	ASTM D445
	Viscosity Index	193		ASTM D2270
	Flashpoint	204	°C	ASTM D92
	Pourpoint	-39	°C	ASTM D6892
	Brookfield Viscosity at -40°C	140000	mPa.s	ASTM D2983