



TQX.30006 Triple QX Gear Oil 75W-90 SEMI SYNPLUS

Documentversie: 18 okt. 2026



Omschrijving Suitable for use in manual gearboxes and hypoid rear axles. Can be used in applications where EP (extreme pressure) gear oils are recommended.

Volgens de specificaties van API GL-5
DAF
DTFR 12B100
MAN 342 Type M-2
MB 235.0
MIL-L-2105D
Renault
Volvo
ZF TE-ML 05A / 07A / 12E / 16B / 17B / 19B / 21A

Verpakkingseenheden	ART. NR.	VOLUME	AANTAL PER STUK	AANTAL PER PALLET
	TQX.522776112	1 L	12	-
	TQX.522776111	5 L	4	-
	TQX.522776115	20 L	1	-
	TQX.522771056	199 L	1	-

Standaardanalyses	TEST	WAARDE		METHODE
	Dichtheid bij 15°C	0.861	kg/l	ASTM D4052
	Kinematische viscositeit bij 40°C	81	mm ² /s	ASTM D445
	Kinematische viscositeit bij 100°C	14.8	mm ² /s	ASTM D445
	Viscositeitsindex	193		ASTM D2270
	Vlampunt	204	°C	ASTM D92
	Vloeipunt	-39	°C	ASTM D6892
	Brookfield-viscositeit bij -40°C	140000	mPa.s	ASTM D2983