



TQX.30007 Triple QX Gear Oil 75W-80 SEMI SYNPLUS

Version du document: 17 oct. 2026



Description	Triple QX 75W-80 GL-5 Gear Oil has been developed to provide superior EP (extreme pressure) protection under the severest of operating conditions in both passenger and commercial vehicles.			
Selon les spécifications de	API GL-4 / GL-5 PSA B71 2330			
Unités d'emballage	ART. N°	VOLUME	ARTICLES PAR UNITÉ	ARTICLES PAR PALETTE
	TQX.522776282	1 L	12	-
	TQX.522776281	5 L	4	-
	TQX.522776285	20 L	1	-
	TQX.522776286	199 L	1	-
Analyses standard	TEST	VALEUR		METHOD
	Densité à 15 °Celsius	0.868	kg/l	ASTM D4052
	Viscosité cinématique à 40 °Celsius	48.5	mm ² /s	ASTM D445
	Viscosité cinématique à 100 °Celsius	8.6	mm ² /s	ASTM D445
	Indice de viscosité	156		ASTM D2270
	Point d'éclair	220	°C	ASTM 92
	Point d'écoulement	-36	°C	ASTM D6892
	Viscosité Brookfield à -40 °Celsius	120000	mPa.s	ASTM D2983

These characteristics are typical of current production. Variations in these characteristics may occur.