

06000PS Motor Oil 0W-40 Pro Street C3

Document version: 16 Mar 2024



Description

According to the specifications of

Packaging units

This premium synthetic fuel economy 'MID SAPS' engine oil has been specially developed for petrol and diesel engines with or without a turbocharger. Due to its good thermal and oxidation stability together with excellent protection against wear and corrosion, it offers optimum engine protection. This MPM Motor Oil 0W-40 Pro Street C3 is suitable for passenger cars and light commercial vehicles equipped with an exhaust after-treatment system.

ACEA C3 API CF / SN

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
06001PS	1 L	6	450
06020PS	20 L	1	30
06060PS	60 L	1	6
06205PS	205 L	1	2
P06000PS	1 L	1	_

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.856	kg/l	ASTM D4052
Viscosity SAE	0W-40 0W-40		
Kinematic Viscosity at 40°C	75.8	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	13.6	mm2/s	ASTM D445
Viscosity Index	185		ASTM D2270
Dynamic Viscosity at -30°C	6600	mPa.s	ASTM D5293
Flashpoint COC	218	°C	ASTM D92
Pourpoint	-42	°C	ASTM D97
Total Base Number	7.5	mgKOH/g	ASTM D2986
Sulphated Ash	0.79	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.