



MPM Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Issue date: 3-7-2019 Revision date: 12-5-2022 Supersedes: 25-4-2022 version: 4.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : MPM Motor Oil 5W-40 Premium Synthetic C3
Product code : 05000C3
Type of product : Other engine, gear and lubricating oils.
Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Consumer use, Industrial use
Industrial/Professional use spec : Non-dispersive use
Used in closed systems
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
Cyclotronweg 1
2629 HN Delft - Nederland
T +31 (0)15 2514030
info@mpmoil.nl - www.mpmoil.com

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains: C14-16-18 Alkylphenol. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

No additional information available.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Highly refined mineral oil, contains <3% (w/w) DMSO extract, according to IP346

MPM Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates(petroleum), hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	≥ 40 – ≤ 60	Asp. Tox. 1, H304
Bis(nonylphenyl)amine	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	≥ 1 – ≤ 2,49	Aquatic Chronic 4, H413
C14-16-18 Alkylphenol	(CAS-No.) 1190625-94-5 (EC-No.) 931-468-2 (REACH-no) 01-2119498288-19	≥ 1 – ≤ 2,49	Skin Sens. 1, H317 STOT RE 2, H373
Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate)	(CAS-No.) 93819-94-4 (EC-No.) 298-577-9 (REACH-no) 01-2119543726-33	≥ 0,1 – ≤ 0,99	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate)	(CAS-No.) 93819-94-4 (EC-No.) 298-577-9 (REACH-no) 01-2119543726-33	(6,25 ≤C < 100) Skin Irrit. 2, H315 (10 ≤C < 12,5) Eye Irrit. 2, H319 (12,5 ≤C < 100) Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation	: Not required.
After skin contact	: Wash skin with mild soap and water.
After eye contact	: In case of eye contact, immediately rinse with clean water for 10-15 minutes.
After ingestion	: Do NOT induce vomiting. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

After inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
After skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
After eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
After ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray, powder, foam and CO2.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available.

5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: If spilled, may cause the floor to be slippery.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Do not breathe vapours.

MPM Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing and gloves. Safety glasses.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Detergent. Clean up any spills as soon as possible, using an absorbent material to collect it.

Other information : Spill area may be slippery. Use suitable disposal containers.

6.4. Reference to other sections

No additional information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Handling temperature : < 40 °C

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a closed container.

Storage conditions : Keep container closed when not in use.

Storage temperature : ≤ 40 °C

Storage area : Store in dry, well-ventilated area.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m³ oilspray (TWA, 8 hour workday) is recommended.

8.2. Exposure controls

Technical measures:

No additional information available.

Personal protective equipment:

Gloves. Safety glasses.

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

Eye protection:

Safety goggles

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

Personal protective equipment symbol(s):



MPM Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily liquid.
Colour	: Amber.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 220 °C @ ASTM D92
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 855 kg/m ³ @ 15°C
Solubility	: Slightly soluble, the product remains on the water surface.
Log Pow	: No data available
Viscosity, kinematic	: 84 mm ² /s @ 40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No naked flames, sparks, and do not smoke.

10.5. Incompatible materials

Strong oxidizing agent. Acids and bases.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates(petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5 mg/l/4h

Bis(nonylphenyl)amine (36878-20-3)

LD50 oral rat	> 5000 mg/kg OECD 401
LD50 oral	> 2000 mg/kg OECD 402

MPM Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)	
LD50 oral rat	2600 mg/kg 67/548/EEG annex V
LD50 dermal rabbit	> 3160 mg/kg bodyweight OECD 402
LC50 Inhalation - Rat	> 2 mg/l 1h OECD 403 -read across

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified. (The component "C14-16-18 alkylphenol" is an impurity of a substance present in the product. On the basis of tests conducted with that substance, the classification as a skin sensitizer of the impurity 'C14-16-18 alkylphenol' is rejected.)
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Distillates(petroleum), hydrotreated heavy paraffinic (64742-54-7)	
NOAEL (dermal, rat/rabbit)	> 2000 mg/kg bodyweight

STOT-repeated exposure : Not classified

Distillates(petroleum), hydrotreated heavy paraffinic (64742-54-7)	
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight/day
NOAEL (subacute, oral, animal/male, 28 days)	> 220 mg/kg bodyweight
NOAEL (subchronic, oral, animal/male, 90 days)	> 980 mg/kg bodyweight

Aspiration hazard : Not classified

MPM Motor Oil 5W-40 Premium Synthetic C3	
Viscosity, kinematic	84 mm ² /s @ 40°C

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Distillates(petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	100 mg/l

Bis(nonylphenyl)amine (36878-20-3)	
LC50 fish 1	> 100 mg/l OECD 203 (Danio rerio @96h)
EC50 Daphnia 1	> 100 mg/l OECD 202 (Daphnia magna)
EC50 72h - Algae [1]	> 100 mg/l OECD 201 (Desmodesmus subspicatus)

Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)	
LC50 fish 1	4,5 mg/l OECD 203 (oncorhynchys mykiss, 96h)
EC50 Daphnia 1	5,4 mg/l OECD 202, (Daphnia magna, 72h)
EC50 72h - Algae [1]	2,1 mg/l Selenastrum capricornutum UTEX 1648

12.2. Persistence and degradability

MPM Motor Oil 5W-40 Premium Synthetic C3	
Persistence and degradability	Not soluble in water, so only minimally biodegradable.

Bis(nonylphenyl)amine (36878-20-3)	
Persistence and degradability	Not readily biodegradable.

MPM Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Biodegradation	1 % @28d
----------------	----------

Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)

Biodegradation	1,5 % OECD 301B 28d
----------------	---------------------

12.3. Bioaccumulative potential

Bis(nonylphenyl)amine (36878-20-3)

Log Pow	> 7,6
---------	-------

Bioaccumulative potential	Bioaccumulation possible.
---------------------------	---------------------------

Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)

Log Pow	0,9 @ 23C
---------	-----------

12.4. Mobility in soil

MPM Motor Oil 5W-40 Premium Synthetic C3

Soil	Prevent soil and water pollution.
------	-----------------------------------

Bis(nonylphenyl)amine (36878-20-3)

Soil	Adsorbs into the soil.
------	------------------------

Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)

Soil	Adsorbs into the soil.
------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available.

12.6. Other adverse effects

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Additional information : This material and its container must be disposed of in a safe way, and as per local legislation.

SECTION 14: Transport information

In accordance with ADR / IMDG

ADR	IMDG
14.1. UN number	
Not applicable	Not applicable
14.2. UN proper shipping name	
Not applicable	Not applicable
14.3. Transport hazard class(es)	
Not applicable	Not applicable
14.4. Packing group	
Not applicable	Not applicable
14.5. Environmental hazards	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

MPM Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains: C14-16-18 Alkylphenol. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.