

BL051000 Marine Gear Oil Propeller Drive

Document version: 17 Mar 2024



Description

This marine gear oil is a mineral gear oil with EP 'extreme pressure' properties which features an optimal tooth flanks protection (Pitting).

This oil is specially designed for use in gearbox transmissions of mechanical clutches and bevel gears of the propeller drive.

SAE 90

According to the specifications of

Packaging units

| 1 | ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|---|----------|--------|----------------|------------------|
| Е | 3L051001 | 1 L | 6 | 450 |
| E | 3L051005 | 5 L | 4 | 112 |
| E | 3L051020 | 20 L | 1 | 30 |
| E | 3L051060 | 60 L | 1 | 6 |
| E | 3L051205 | 205 L | 1 | 2 |
| E | 3L051999 | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|-------|-------|--------|
| Density at 15°C | 0.897 | kg/l | |
| Kinematic Viscosity at 40°C | 145 | mm2/s | |
| Kinematic Viscosity at 100°C | 14.4 | mm2/s | |
| Viscosity Index | 97 | | |
| Flashpoint COC | 210 | °C | |
| Pourpoint | -30 | °C | |

These characteristics are typical of current production. Variations in these characteristics may occur.